




DIAPHRAGM PUMP 2" ALUMINIUM-VITON-VITON ATEX

 Diaphragm pump 2 Aluminium-VITON-VITON ATEX

Part No
UP20A-CAC-AVV

TECHNICAL DATA

DIAPHRAGM PUMP 2" ALUMINIUM-VITON-VITON ATEX

SAMOA diaphragm pump - compressed air driven for stationary or portable use. Can run dry without damage and requires no electrical connection. Depending on the material selected, handles both clean, dirty, corrosive and abrasive liquids. Automatic start/s

TECHNICAL DATA	
Part No	UP20A-CAC-AVV
Ratio	1:1
Capacity	650 l/min free flow
Air connection	3/4" (F) NPT
Maximum air pressure	0,8 (8) MPa (bar)
Inlet	2" Flange DIN/ANSI
Outlet	2" Flange DIN/ANSI
Seals	FKM / Viton®
Max suction height	8 m
Max particle size	6,4 (1/4) mm (inch)
Material pump body	Aluminium
Material diaphragm	FKM / Viton®
Material balls	FKM / Viton®
Material ball valve seats	Aluminium
Certification	Ex II2 GD IIB/IIC 95 °C
Weight (Gross)	54 kg
H.S. Code	84138100