

DIAPHRAGM PUMP 1 1/2" PP-SANTOPRENE- SANTOPRENE



Part No
UP15P-FPS-PMA

TECHNICAL DATA

DIAPHRAGM PUMP 1 1/2" PP-SANTOPRENE-SANTOPRENE

SAMOA diaphragm pump - compressed air driven for stationary or portable use. Can run dry without damage and requires no electrical connection. Depending on the material selected, handles both clean, dirty, corrosive and abrasive liquids. Automatic start/s

TECHNICAL DATA	
Part No	UP15P-FPS-PMA
Ratio	1:1
Capacity	475 l/min free flow
Air connection	1/2" (F) NPT
Maximum air pressure	0,8 (8) MPa (bar)
Inlet	1 1/2" Flange DIN/ANSI
Outlet	1 1/2" Flange DIN/ANSI
Seals	Santoprene®
Max suction height	9 m
Max particle size	6,4 (1/4) mm (inch)
Material pump body	Polypropylene
Material diaphragm	Santoprene®
Material balls	Santoprene®
Material ball valve seats	Polypropylene
Weight (Gross)	21,9 kg
H.S. Code	84138100

RELATED PRODUCTS

PART NO	DESCRIPTION	
UP15R-WP-P00	Valve seat kit, polypropylene for UP15P	
UP15R-AM-1P0	Air motor kit for UP15P	
UP15R-WP-99E	Seat O-ring kit EPDM for UP15	
UP15R-WP-00A	Diaphragm kit Santoprene for UP15	
UP15R-AM-200	Air sensor kit for UP15	
28515	Needle valve 1/2" (F)-(M) BSP Compressed air Brass	
42121	Filter/Regulator 1/2" (F) BSP	
853443	Adaptor straight 1/2" (F) BSP-(M) NPT	
UP15R-WP-0M0	Ball kit Santoprene for UP15	