

## DIAPHRAGM PUMP 1 1/2" PP-PTFE-PTFE



Part No  
UP15P-CPS-PTZ

## TECHNICAL DATA

### DIAPHRAGM PUMP 1 1/2" PP-PTFE-PTFE

SAMOA diaphragm pump - compressed air driven for stationary or portable use. Can run dry without damage and requires no electrical connection. Depending on the material selected, handles both clean, dirty, corrosive and abrasive liquids. Automatic start/s

TECHNICAL DATA	
Part No	UP15P-CPS-PTZ
Ratio	1:1
Capacity	475 l/min free flow
Air connection	1/2" (F) NPT
Maximum air pressure	0,8 (8) MPa (bar)
Inlet	1 1/2" Flange DIN/ANSI
Outlet	1 1/2" Flange DIN/ANSI
Seals	PTFE / Teflon®
Max suction height	9 m
Max particle size	6,4 (1/4) mm (inch)
Material pump body	Polypropylene
Material diaphragm	PTFE / Teflon®
Material balls	PTFE / Teflon®
Material ball valve seats	Polypropylene
Weight (Gross)	29,4 kg
H.S. Code	84138100

**RELATED PRODUCTS**

PART NO	DESCRIPTION	
UP15R-WP-99T	Seat O-ring kit PTFE for UP15	
UP15R-WP-P00	Valve seat kit, polypropylene for UP15P	
853443	Adaptor straight 1/2" (F) BSP-(M) NPT	
APD20B-FPS-Z	Pulsation damper 2" Polypropylene-PTFE	
28515	Needle valve 1/2" (F)-(M) BSP Compressed air Brass	
UP15R-WP-0T0	Ball kit PTFE for UP15	
42121	Filter/Regulator 1/2" (F) BSP	
UP15R-AM-200	Air sensor kit for UP15	
UP15R-WP-00H	Diaphragm kit PTFE for UP15P	
UP15R-AM-1P0	Air motor kit for UP15P	