



DIAPHRAGM PUMP 1/2" ALUMINIUM-FKM-FKM ATEX



Part No
UP05A-BAC-AVV




TECHNICAL DATA

DIAPHRAGM PUMP 1/2" ALUMINIUM-FKM-FKM ATEX

SAMOA diaphragm pump - compressed air driven for stationary or portable use. Can run dry without damage and requires no electrical connection. Depending on the material selected, handles both clean, dirty, corrosive and abrasive liquids. Automatic start/s

TECHNICAL DATA	
Part No	UP05A-BAC-AVV
Ratio	1:1
Capacity	54 l/min free flow
Air connection	1/4" (F) NPSM
Maximum air pressure	0,8 (8) MPa (bar)
Inlet	1/2" (F) BSP
Outlet	1/2" (F) BSP
Seals	FKM / Viton®
Max suction height	8 m
Max particle size	2,5 (3/32") mm (inch)
Material pump body	Aluminium
Material diaphragm	FKM / Viton®
Material balls	FKM / Viton®
Material ball valve seats	Aluminium
Certification	Ex II2 GD IIB/IIC 95 °C
Weight (Gross)	4,40 kg
H.S. Code	84138100

RELATED PRODUCTS

PART NO	DESCRIPTION	
UP05R-AM-1A0	Air motor kit for UP05A	
360101	Wall bracket for diaphragm pump UP03, UP05, CP10, DF100	
UP05R-WP-00V	Diaphragm kit FKM for UP05	
UP05R-WP-99V	Seat O-ring kit FKM / Viton® for UP05	
UP05R-AM-200	Air sensor kit for UP05	
42107	Filter-Regulator incl. gauge 1/4" (F) BSP	
42131	Regulator with pressure gauge 1/4" (F) BSP	
28513	Needle valve 1/4" (F)-(M) BSP Compressed air Brass	
UP05R-WP-A00	Seat kit Aluminium for UP05A	
UP05R-WP-0V0	Ball kit FKM, for UP05	