

DIAPHRAGM PUMP 1" PVDF-PTFE-PTFE



Part No
UP10B-BWS-WTZ

TECHNICAL DATA

DIAPHRAGM PUMP 1" PVDF-PTFE-PTFE

SAMOA diaphragm pump - compressed air driven for stationary or portable use. Can run dry without damage and requires no electrical connection. Depending on the material selected, handles both clean, dirty, corrosive and abrasive liquids. Automatic start/s

TECHNICAL DATA	
Part No	UP10B-BWS-WTZ
Ratio	1:1
Capacity	200 l/min free flow
Air connection	1/2" (F) BSP
Maximum air pressure	0,7 (7) MPa (bar)
Inlet	1" (F) BSP
Outlet	1" (F) BSP
Seals	PTFE / Teflon®
Max suction height	8 m
Max particle size	6,4 (1/4) mm (inch)
Material pump body	PVDF / Kynar / Solef
Material diaphragm	PTFE / Teflon®
Material balls	PTFE / Teflon®
Material ball valve seats	PVDF / Kynar / Solef
Weight (Gross)	14 kg
H.S. Code	84138100

RELATED PRODUCTS

PART NO	DESCRIPTION	
UP10R-AM-201	Air sensor kit for UP10B	
28515	Needle valve 1/2" (F)-(M) BSP Compressed air Brass	
853443	Adaptor straight 1/2" (F) BSP-(M) NPT	
42121	Filter/Regulator 1/2" (F) BSP	
UP10R-WP-0T0	Ball kit PTFE for UP10	
UP10R-WP-99T	Seat O-ring kit PTFE for UP10	
UP10R-WP-00Z	Diaphragm kit PTFE for UP10	
42132	Regulator with pressure gauge 1/2" (F) BSP	
UP10R-AM-300	Air shaft kit, for UP10	
UP10R-AM-1B0	Air motor kit for UP10B	